

# Centrify Server Suite 2017

## *Upgrade and Compatibility Guide*

February 2017

Centrify Corporation



• • • • •

## Legal notice

This document and the software described in this document are furnished under and are subject to the terms of a license agreement or a non-disclosure agreement. Except as expressly set forth in such license agreement or non-disclosure agreement, Centrifly Corporation provides this document and the software described in this document “as is” without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose. Some states do not allow disclaimers of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This document and the software described in this document may not be lent, sold, or given away without the prior written permission of Centrifly Corporation, except as otherwise permitted by law. Except as expressly set forth in such license agreement or non-disclosure agreement, no part of this document or the software described in this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, or otherwise, without the prior written consent of Centrifly Corporation. Some companies, names, and data in this document are used for illustration purposes and may not represent real companies, individuals, or data.

This document could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These changes may be incorporated in new editions of this document. Centrifly Corporation may make improvements in or changes to the software described in this document at any time.

© 2004-2017 Centrifly Corporation. All rights reserved. Portions of Centrifly software are derived from third party or open source software. Copyright and legal notices for these sources are listed separately in the Acknowledgements.txt file included with the software.

U.S. Government Restricted Rights: If the software and documentation are being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), in accordance with 48 C.F.R. 227.7202-4 (for Department of Defense (DOD) acquisitions) and 48 C.F.R. 2.101 and 12.212 (for non-DOD acquisitions), the government’s rights in the software and documentation, including its rights to use, modify, reproduce, release, perform, display or disclose the software or documentation, will be subject in all respects to the commercial license rights and restrictions provided in the license agreement.

Centrifly, DirectControl, DirectAuthorize, DirectAudit, DirectSecure, DirectControl Express, Centrifly User Suite, and Centrifly Server Suite are registered trademarks and Centrifly for Mobile, Centrifly for SaaS, Centrifly for Mac, DirectManage, Centrifly Express, DirectManage Express, Centrifly Identity Platform, Centrifly Identity Service, and Centrifly Privilege Service are trademarks of Centrifly Corporation in the United States and other countries. Microsoft, Active Directory, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries.

Centrifly software is protected by U.S. Patents 7,591,005; 8,024,360; 8,321,523; 9,015,103 B2; 9,112,846; 9,197,670; and 9,378,391.

The names of any other companies and products mentioned in this document may be the trademarks or registered trademarks of their respective owners. Unless otherwise noted, all of the names used as examples of companies, organizations, domain names, people and events herein are fictitious. No association with any real company, organization, domain name, person, or event is intended or should be inferred.



# Contents

## About this guide

Intended audience .....	5
Using this guide .....	5
Conventions used in this guide .....	6
Finding more information .....	6
Contacting Centrify .....	7
Getting additional support .....	7

## Chapter 1 Preparing for an upgrade

Upgrading the operating system .....	8
Upgrading computers that are accessed by multiple users .....	8
General compatibility between versions of Centrify software .....	9
Finding upgrade packages .....	10
Disabling command-line auditing .....	11

## Chapter 2 Upgrading DirectManage on Windows computers

What should you upgrade first? .....	12
Updating administrative components .....	12
Upgrading components interactively .....	14
Upgrading auditing components silently on Windows .....	14

## Chapter 3 Upgrading the auditing infrastructure

Why there are formal steps for upgrading an audit installation .....	16
Upgrading auditing components in a specific order .....	16
Unsupported configurations .....	17
Updating auditing-related databases .....	17
Updating agents out of sequence .....	18
Restarting a computer after an agent upgrade .....	19



Chapter 4	<b>Upgrading managed computers</b>	
	Using Deployment Manager to update agents . . . . .	20
	Using the install.sh shell script to update packages . . . . .	21
	Using a native package manager on Linux computers. . . . .	23
	Using a native package manager on UNIX computers . . . . .	26
	Upgrading managed Mac OS X computers. . . . .	32
Chapter 5	<b>Compatibility for additional packages</b>	
	Should you be concerned about compatibility? . . . . .	33
	Removing the CentrifyDC-samba package . . . . .	34
	Compatibility for CentrifyDC-nis package. . . . .	34
	Compatibility for CentrifyDC-krb5 package . . . . .	35
	Compatibility for CentrifyDC-ldapproxy package . . . . .	35
	Compatibility for CentrifyDC-openssh package. . . . .	35
	Compatibility for CentrifyDC-apache and CentrifyDC-web packages. . . . .	36
	Upgrading version-dependent packages . . . . .	36
	Working with classic zones after an upgrade. . . . .	36
Chapter 6	<b>What to do if there are problems during an upgrade</b>	
	Remove and re-install DirectManage Access . . . . .	38
	Remove and re-install DirectManage Audit . . . . .	38
	Remove and re-install agent features . . . . .	39

## Index

# About this guide

The *Centrify Server Suite Upgrade and Compatibility Guide* describes how to upgrade Centrify components on computers where Centrify software has been previously installed. In most cases, components and software packages from different releases can be used together within certain limitations.

This guide provides guidelines for the order in which you should upgrade, compatibility issues that might require you to upgrade, and how you can mix and match component and package versions if you perform an upgrade over time on computers running different versions of Centrify packages.

## Intended audience

This guide is intended for administrators and application owners planning to update Centrify software on multiple computers in the enterprise. This guide assumes that you are familiar with all of the Centrify components you have currently installed on one or more Windows computers and all of the required and optional packages you have installed on Linux, UNIX, and Mac OS X computers. This guide also assumes that you have sufficient privileges to perform administrative tasks on all of these computers.

## Using this guide

Depending on your role and responsibilities, you may want to read portions of this guide selectively.

The guide provides the following information:

- **Chapter 1, “Preparing for an upgrade,”** provides an overview of the recommended upgrade process and a summary of the compatibility requirements between the core components of Centrify software.
- **Chapter 2, “Upgrading DirectManage on Windows computers,”** describes the upgrade steps for the access control and privilege

management components you have installed on Windows computers.

- **Chapter 3, “Upgrading the auditing infrastructure,”** describes the recommended upgrade path for the auditing infrastructure, including the databases, to ensure auditing is not interrupted.
- **Chapter 4, “Upgrading managed computers,”** describes the upgrade steps for the components you have installed on managed computers.
- **Chapter 5, “Compatibility for additional packages,”** provides additional information about the compatibility between core components and other packages you may have installed on managed computers.
- **Chapter 6, “What to do if there are problems during an upgrade,”** suggests the steps to take if you encounter errors that prevent you from upgrading.

## Conventions used in this guide

The following conventions are used in this guide:

- `Fixed-width` font is used for sample code, program names, program output, file names, and commands that you type at the command line. When *italicized*, the fixed-width font is used to indicate variables.
- **Bold** text is used to emphasize commands, buttons, or user interface text, and to introduce new terms.
- *Italics* are used for book titles and to emphasize specific words or terms.

## Finding more information

Centrify provides extensive documentation targeted for specific audiences, functional roles, or topics of interest. If you want to learn more about Centrify and Centrify products and features, start by visiting the [Centrify website](#). From the Centrify website, you can download data sheets and evaluation software, view video demonstrations and technical presentations about Centrify products, and get the latest news about upcoming events and webinars.

For access to documentation for all Centrify products and services, visit the [Centrify documentation portal](#). From the Centrify documentation portal, you can always view or download the most up-to-date version of this guide and all other product documentation.

To get to the documentation portal, go to [docs.centrify.com](https://docs.centrify.com) or <https://www.centrify.com/support/documentation>.

## Contacting Centrify

You can contact Centrify by visiting our website, [www.centrify.com](http://www.centrify.com). On the website, you can find information about Centrify office locations worldwide, email and phone numbers for contacting Centrify sales, and links for following Centrify on social media. If you have questions or comments, we look forward to hearing from you.

## Getting additional support

If you have a Centrify account, click Support on the Centrify website to log on and access the [Centrify Technical Support Portal](#). From the support portal, you can search knowledge base articles, open and view support cases, download software, and access other resources.

To connect with other Centrify users, ask questions, or share information, visit the [Centrify Community](#) website to check in on customer forums, read the latest blog posts, view how-to videos, or exchange ideas with members of the community.

# Preparing for an upgrade

This chapter provides an overview of the upgrade process and a summary of the compatibility requirements between the core components of Centrify software. You should review the information in this chapter before upgrading any components on the computers where Centrify software is installed.

## Upgrading the operating system

Upgrading the operating system (OS) on a managed computer can make major changes to the configuration files and utilities installed on it. In many cases, operating system upgrades and operating system patches can change the behavior of Centrify software. If the behavior of Centrify software is modified because of an operating system upgrade, it is possible for users to be locked out and unable to access computer resources. To prevent this from happening, Centrify recommends that you first remove any Centrify packages you have installed before upgrading the operating system, then reinstall the packages after the operating system upgrade has been completed and the computer has been verified to be operating normally.

You should note that removing Centrify software prior to applying operating system patches or upgrading the operating system is not required in most cases. However, because operating system changes can affect authentication and authorization services, it is considered a best practice to ensure the upgrade does not interrupt services for any users.

## Upgrading computers that are accessed by multiple users

In most cases, you can upgrade Centrify software on computers that are accessed by multiple users without entering single-user mode. However, upgrading authentication, authorization, and auditing services on a computer can potentially prevent users from logging on



or using computer resources. If possible, you should perform upgrades when other users who might access the computer are logged off, then reboot the computer after completing the upgrade.

You should note that having all users logged off and rebooting the computer after an upgrade are not required steps, but are best practices to ensure the upgrade does not interrupt services for any users. In most cases, users who are already logged on are not affected by the upgrade. However, users who attempt to log on while files are being replaced during the upgrade process might be temporarily locked out of the managed computer you are upgrading.

## General compatibility between versions of Centrify software

In most cases, newer versions of Centrify software releases are backward-compatible with previous versions, enabling you to mix and match components from different versions and upgrade components over time when it is convenient to do so. However, there are some limitations to take into account when mixing and matching versions, and these limitations might influence which components you upgrade and how quickly you upgrade from one version to another.

In most organizations, the agents you install on managed computers are upgraded on a staggered schedule while administrative tools are upgraded at a set time to take advantage of new features.

To ensure flexibility of the upgrade process:

- Agents are always backward-compatible with older versions of the administrative console.

However, using an older version of the administrative console with a newer agent limits the features and functionality available. If you are using an administrative console from version 2.x to manage zones, agents from version 4.x and 5.x must use the `--compat` option to join 2.x-compatible zones.

- Agents are always forward-compatible with the administrative console for one version.

You can upgrade the administrative console without upgrading agents at the same time. However, there are limitations to features and functionality when using older agents with an upgraded console. For example, agents from version 4.x cannot be included in hierarchical zones. In addition, some features require an upgrade. For example, if you want to use the Centrify agent for Windows for access control and privilege management, you must either upgrade or remove the Centrify auditing service for Windows.

- Group policies are not guaranteed to be compatible with different agent and administrative console versions.

New group policies cannot be enforced on computers with an agent from a previous version of Centrify software. If a group policy is applied to a computer that has an older version of the agent, the policy is ignored. You should only apply group policies that are supported in both the agent and administrative console versions you are using.

## Finding upgrade packages

You can find Centrify Server Suite and agent packages for all supported operating systems on the [Centrify Customer Download Center](#). From the Customer Download Center, you can choose to download individual agent packages one at a time or download an archive that includes agents for all operating systems at once.

At a minimum, you should download the Centrify Agent Installer and the ADCheck Diagnostic Tool. You can then use the `install.sh` shell script interactively or with the `centrify-suite.cfg` configuration file to install and enable features on the computers you want to upgrade.

Centrify recommends that you use the `install.sh` shell script to install or upgrade all Centrify packages on managed computers, especially if you have multiple Centrify packages installed that you wish to upgrade. The `install.sh` installation script performs a thorough set of pre-installation and post-installation steps to ensure a successful installation or upgrade with minimal disruption to your environment.

Alternatively, you can use the native package manager for your operating system to upgrade the components you have installed. If you want to use a native package manager, see [“Using a native package manager on Linux computers” on page 23](#) for Linux computers or [“Using a native package manager on UNIX computers” on page 26](#) for UNIX computers.

## Disabling command-line auditing

If you have auditing enabled on a computer you are upgrading, you should check whether auditing is configured for individual commands or all user activity. If you have enabled auditing for specific commands, you should temporarily disable auditing on the managed computer before upgrading, then restart the auditing of individual commands after completing the upgrade. If you are auditing all user activity on a managed computer, you do not need to stop the auditing service. There will be a brief interruption while files are replaced, then auditing will continue without requiring you to manually restart it.

# Upgrading DirectManage on Windows computers

This chapter describes how to upgrade DirectManage Access and DirectManage Audit administrative components on Windows computers. It includes a more detailed discussion about compatibility between components.

## What should you upgrade first?

You are not required to upgrade Centrify software components in any particular order. Depending on where you have components installed and how they are distributed, you might update components used for auditing before updating components for access control and privilege management. Alternatively, you might update one set of agents immediately, followed by one administrative console, then update other components at a later time.

Although there's no technical requirement to upgrade components in a specific order, most organizations upgrade one or more administrative consoles and components that might require changes to a database first—for example, DirectManage Access Manager and DirectManage Deployment Manager if upgrading access control and privilege management—then deploy upgraded agent software after upgrading all of other components.

Similarly, if you upgrading the auditing infrastructure, you might upgrade DirectManage Audit Manager, the management database, and the audit store before upgrading collectors and agents.

## Updating administrative components

As noted in [“General compatibility between versions of Centrify software” on page 9](#), most organization upgrade the administrative consoles at a set time, often as part of planned maintenance, then upgrade agents opportunistically over a period of time. It is common, therefore, to have a mix of components from different versions of Centrify software within certain limits.

To help you plan for the upgrade, you should identify which versions of different components you currently have installed and which components will require an upgrade.

Depending on whether you are upgrading DirectManage Access, DirectManage Audit, or both feature sets, you might have different compatibility requirements.

## Access control and privilege management compatibility

You can upgrade to Centrify Server Suite—with DirectManage Access Manager, version 5.1.x or later—to manage zones and agents (`adclient`) from version 3.x, 4.x, or 5.x. If you have agents from version 2.x, you must manage them using a console from version 4.x or earlier. If you use an older version of the console, you cannot take advantage of any features or enhancements introduced in newer versions of the console. If you upgrade to the latest release, you can continue to manage all of your currently deployed agents but must upgrade those agents to take full advantage of any new features.

You must upgrade UNIX, Linux, or Mac agents to 5.0 or later to use hierarchical zones. If you have zones from a previous release of Centrify software, you can use `admigrate` to convert those zones to hierarchical zones.

To manage Windows computers with DirectManage Access Manager, the Centrify Windows agent must be version 3.0 or later.

## Auditing infrastructure compatibility

You can upgrade to Centrify Server Suite—with DirectManage Audit Manager, Audit Analyzer, and Collector service version 3.1.x or later—to manage auditing on UNIX, Linux, and Windows computers from version 2.x or 3.x. If you have agents from version 1.x, you must manage them using a console from version 1.x. You can, however, make data collected by 1.x agents available for viewing in the Audit Analyzer console by attaching the 1.x database to an updated audit store.

You must update the collector service to version 3.x to receive audit data from Windows computers with 3.x Windows agents.

Because the auditing infrastructure is a multi-tiered architecture that collects information to be preserved, reviewed, and archived, Centrify recommends a more formal upgrade process than for other components. This is especially true for larger organizations that collect a great deal of audit data. If you are upgrading the auditing infrastructure, therefore, see [“Upgrading the auditing infrastructure” on page 16](#) for more detailed information about the process to follow.

## Upgrading components interactively

You can upgrade components on any Windows computer interactively by clicking the links on the Centrify Server Suite Getting Started page. If the DirectManage Access setup program detects components are installed, you have the option to update, modify, or remove those components. You can then follow the prompts displayed to review the components to be updated and complete the upgrade.

If the DirectManage Audit setup program detects components are installed, you are prompted to confirm that you want to continue with the upgrade. You can then follow the prompts displayed to review the components to be updated and complete the upgrade.

## Upgrading auditing components silently on Windows

If you want to perform a “silent” or unattended installation of the Centrify auditing components, you can do so by specifying the appropriate command line options and Microsoft Windows Installer (MSI) file to deploy. You can also use an unattended installation to automate the installation or upgrade on remote computers if you use a software distribution product, such as Microsoft System Center Configuration Manager (SCCM), to deploy software packages.

If you have the physical CD or ISO image for Centrify software, you can find the Microsoft Windows Installer (MSI) files for auditing components in subdirectories under the DirectAudit folder.

Before running the Microsoft Windows Installer (MSI) for any component, you should verify the computers where you plan to install meet the prerequisites described in the auditing administrator's guide.

To install the auditing components silently:

- 1 Open a Command prompt window or prepare a software distribution package for deployment on remote computers.

For information about preparing to deploy software on remote computers, see the documentation for the specific software distribution product you are using. For example, if you are using Microsoft System Center Configuration Manager (SCCM), see the Configuration Manager documentation.

- 2 Select the appropriate package for the auditing component you want to upgrade.

For example, locate the following file to install the audit management server on 64-bit operating systems:

```
Centrify DirectAudit Audit Management Server64.msi
```

- 3 Run the installer with no user interface and specify the package for the auditing component you want to upgrade.

For example, to upgrade an agent on 64-bit operating systems, run the following command:

```
msiexec /qn /i "Centrify Windows Agent64.msi"
```

# Upgrading the auditing infrastructure

This chapter describes the recommended steps for upgrading auditing-related components to ensure you can continue auditing activity throughout the upgrade process. Keep in mind that upgrading the auditing infrastructure might require updates to the existing database, but, in most cases, should not require any computers to be shutdown or restarted to complete the upgrade.

## Why there are formal steps for upgrading an audit installation

In most organizations that deploy auditing, the auditing infrastructure—the installation—consists of components on multiple computers that must be able to communicate with each other to collect, transfer, and store information about user and computer activity. This multi-tiered architecture might be widely distributed and might include hundreds or thousands of computers that must be monitored. Upgrading all of those computers without interrupting ongoing auditing service requires a formal upgrade process that allows computers from different versions to continue communicating for a period of time.

## Upgrading auditing components in a specific order

Because the upgrade process is expected to take a period of time—the length of time depends on the size and complexity of your installation—there are specific rules about the configurations supported and the order in which you should upgrade auditing components.

To ensure auditing continues uninterrupted during the upgrade period, you should upgrade audit installation components in the following order:



- Audit store databases
- Management server databases
- Consoles and collectors and the management server service
- Agents

By following this upgrade order, you can ensure components can continue to communicate while you upgrade the rest of the audit installation. For example, an upgraded audit store can continue to receive audit data from collectors and respond to requests from the management server and consoles that have not been updated.

Be sure to upgrade all of your audit store databases before upgrading other components. You can upgrade the database without upgrading other components from a Command window by running the following command:

```
setup.exe /database
```

## Unsupported configurations

If you upgrade auditing components in a different sequence than the one described in [“Upgrading auditing components in a specific order” on page 16](#), you might end up with an unsupported configuration that requires you to upgrade the remaining components immediately or suspend auditing of user activity until you can complete the upgrade.

You might encounter this situation if you upgrade the Audit Manager and Audit Analyzer consoles or a collector before upgrading the management and audit store databases.

## Updating auditing-related databases

If an upgrade requires an update to the database, you are prompted to run the database maintenance wizard and to select the databases to upgrade. If the wizard can connect to the databases selected and the database upgrade is successful, no further action is required.

You can upgrade audit store databases and the management database interactively using the Database Maintenance Wizard or by running the following command:

```
setup.exe /database
```

Upgrading the auditing databases, however, requires specific Windows and database permissions. Before attempting to upgrade the database, verify you have a user account that meets the following requirements:

- The Windows account you use to update the database with the Database Maintenance Wizard must be an Active Directory domain user and a local administrator on computer where you are running the `setup.exe` program.
- Your Windows or SQL login account must be either a member of `sysadmin` fixed server role or a member of `db_owner` database role on each of the database instances being upgraded. If the account is a member of `db_owner` database role, you must also have the `EXTERNAL ACCESS ASSEMBLY` permission on each of the database servers hosting the management database and audit store databases.

You can use the following SQL statement to grant the `EXTERNAL ACCESS ASSEMBLY` permission to a specific user:

```
GRANT EXTERNAL ACCESS ASSEMBLY TO [DOMAIN\user]
```

For example, to grant this permission to the account `john@acme.com`, you might execute the following SQL statement:

```
GRANT EXTERNAL ACCESS ASSEMBLY TO [ACME\john]
```

## Updating agents out of sequence

The recommended upgrade steps suggest that you to update deployed agents last. However, upgrading the agent is much simpler than upgrading the audit store or management database. which might require a database administrator to be involved. In most cases, it is safe to update the agent at any point in the upgrade process. If there are restrictions that would prevent a new agent from using an older

collector, those restrictions are documented in the release notes you received with the package.

## Restarting a computer after an agent upgrade

If a computer has both Access and Audit features enabled, you must restart the computer after upgrading the agent. If a computer only has auditing features enabled, there's no requirement to restart.

# Upgrading managed computers

This chapter describes how to update Centrify software on managed Linux and UNIX computers. You can also upgrade Centrify software on Mac OS X computers using the `install.sh` shell script in a Terminal application or by downloading, unpacking, and running the latest Mac OS X installer. For more information about upgrading Centrify software on Mac OS X computers, see the *Administrator's Guide for Mac OS X*.

## Using Deployment Manager to update agents

You can use DirectManage Deployment Manager to automatically or manually download updated Centrify software, check whether remote computers are prepared to receive software updates, and deploy updated software from a central console on a Windows computer. Although you can perform other administrative tasks from Deployment Manager, it is intended primarily to simplify the deployment of new and updated Centrify agents with default configuration options.

If you are only interested in updating the Centrify agent and default packages, such as the Centrify-enabled OpenSSH, you should use Deployment Manager to perform the upgrade. For information about using Deployment Manager, see the *Deployment Manager User's Guide* or the *Planning and Deployment Guide*.

If you don't have access to a Windows computer with Deployment Manager or have restricted network connectivity that prevents you from using Deployment Manager, you can use the `install.sh` shell script or a native package manager to update Centrify software. You might also want to use the `install.sh` shell script instead of Deployment Manager if you have packages other than the Centrify agent that you want to upgrade or if you want to manually select which packages are upgraded.

## Using the `install.sh` shell script to update packages

The Centrify agent installation script, `install.sh`, is a shell script that you can run interactively or configure to run silently on any supported UNIX, Linux, or Mac OS X computer.

You can use the `install.sh` shell script to upgrade any installed Centrify software except Centrify DirectSecure and Centrify `sudo`. If you have DirectSecure installed on a managed computer, you should stop the service prior to upgrading the Centrify agent. You can then upgrade DirectSecure after you have upgraded the Centrify agent and other packages. The DirectSecure service and the Centrify agent should be kept synchronized at the same version level.

If you have the Centrify `sudo` package, you can upgrade the package before or after you upgrade the Centrify agent and other packages.

To use the `install.sh` script interactively:

- 1 Unzip and extract the contents of the file you downloaded from the Centrify Corporation Customer Download Center. For example:

```
gunzip centrify-suite-release.update-platform-arch.tgz
tar -xvf centrify-suite-release.update-platform-arch.tar
```

- 2 Run the `install.sh` script to start the update on the local computer's operating environment. For example:

```
./install.sh
```

The installer checks that it is possible to update Centrify software on the local computer. For example, it will check that the computer is a supported platform and that any required patches are installed. For more information about the ADCheck diagnostic tool, see the *Planning and Deployment Guide*.

- 3 Specify the type of upgrade you want to perform.
  - Standard (S) edition upgrades Centrify Server Suite access control (DirectControl), privilege management (DirectAuthorize), and secure shell (Centrify-enabled OpenSSH) features. Any other Centrify packages you have installed are unchanged as long as they are compatible with the version being upgraded.

- Enterprise (E) edition upgrades Centrify Server Suite access control, privilege management, secure shell, and auditing (DirectAudit) features. Any other Centrify packages you have installed are unchanged as long as they are compatible with the version being upgraded.
- Custom (C) option allows you to select the Centrify packages located in the current directory and choose whether to erase (E), update (U), replace (R), keep unchanged (K) each package. If there is a package available for which there is no corresponding version already installed, you can choose to install (I) the package.
- Express (X) installs or upgrades the standard edition components as unlicensed Centrify Express components.

If you want to install or upgrade additional packages such as the Centrify Network Information Service (`adnisd`) or the Centrify LDAP proxy service, you should use the custom install option and select the packages to install.

## Configuring `install.sh` to run without user interaction

You can use the `install.sh` shell script to upgrade computers silently without user interaction. When you run `install.sh` without user interaction, you have the same standard, enterprise, and custom upgrade options that you have when using `install.sh` interactively. When using `install.sh` without user interaction, however, you specify the type of upgrade on the command line and in a configuration file.

`--std-suite` upgrades Centrify Server Suite access control and privilege management features. Any other Centrify packages you have installed are unchanged as long as they are compatible with the version being upgraded.

`--ent-suite` upgrades Centrify Server Suite access control, privilege management, and auditing features. Any other Centrify packages you have installed are unchanged as long as they are compatible with the version being upgraded.

In both cases, you can customize the upgrade by modifying the default `centrify-suite.cfg` configuration file. With the default `centrify-suite.cfg` configuration file, the `install.sh` script upgrades the Centrify agent access control and privilege management features or the Centrify access control, privilege management, and auditing features (if you specify the `--ent-suite` option).

All other packages available are left unchanged. For more detailed information about configuring a silent upgrade using the configuration file, see “Setting the parameters in a custom configuration file for the installation script” and the details for the `INSTALL` parameter in the *Planning and Deployment Guide*.

**Note** If you run the `install.sh` script with the `--std-suite` option, the settings for `CentrifyDC-nis` and `CentrifyDA` packages are ignored.

## Using a native package manager on Linux computers

When you upgrade using the Centrify `install.sh` shell script, the script manages all dependencies and compatibility issues for you. If you want to upgrade Centrify software packages using the native package manager, you should first determine whether there are any compatibility issues or dependencies between the packages you have installed. For details about specific version compatibility requirements and upgrade scenarios, see “[Compatibility for additional packages](#)” on [page 33](#).

As of version 5.4.0, the core Centrify agent bundle consists of four packages that must always be upgraded to the same version simultaneously: `CentrifyDC`, `CentrifyDC-openssl`, `CentrifyDC-openldap`, and `CentrifyDC-curl`. When fixes and patches are released, you can update individual packages of the core bundle, as long as the version is the same version as the other core packages.

After you have determined whether you have any version dependencies, you can use the native package manager to upgrade packages simultaneously. You can also use the native package manager to remove old packages individually or remove all packages simultaneously.

If you want to install or upgrade software packages using common native package installers, such as the Red Hat or Debian package manager, you should note that the software packages are signed with a GNU Privacy Guard (GPG) key. You need to import the key to verify the package authenticity before installing or upgrading the package. To import the key, download the `RPM-GPG-KEY-centrify` file from the Centrify Download Center then run the appropriate command for the package manager. For example:

```
rpm --import RPM-GPG-KEY-centrify
```

If you are not using a native package manager, you can use any other installation program you have available for the local operating environment. For example, if you use another program, such as SMIT, YAST, APT, or YUM to install and manage software packages, you can use that program to install Centrify Server Suite software packages.

## Upgrading packages on a Linux computer

You do not need to stop any running Centrify process to perform the upgrade. While you do not usually need to restart Centrify processes or reboot your computer after upgrade, you may need to restart other processes that depend on PAM or NSS modules. Rebooting the computer after upgrade is recommended as a best practice.

It is best to install all Centrify packages simultaneously, if you are upgrading individual packages, however, you might see warnings from the package manager about package dependencies or version conflicts. If you see that a dependency is generated because of a package you have yet to upgrade, it is safe to ignore the warning.

### Fresh install using RPM

If you are performing a fresh installation on a Linux computer that supports the Red Hat Package Manager (rpm), you can install the packages individually. For example, to install the Centrify DirectAudit package you would enter commands similar to the following:

```
rpm -i CentrifyDA-5.4.0-platform.arch.rpm
```

The platform and architecture you specify in the file name on the command line should identify the specific operating system you are using, for example `CentrifyDC-5.4.0-rhel4.x86_64.rpm` or



CentrifyDC-5.4.0-suse10.ia64.rpm. After the package manager updates the packages installed, you can optionally restart Centrify processes or reboot the computer.

You can verify the Centrify packages that were installed using the following command:

```
rpm -qa CentrifyDC-*
```

## Upgrading existing packages using RPM

If you are upgrading an existing installation of an agent package on a Linux computer that supports the Red Hat Package Manager (rpm), you should add all of the packages you want to upgrade to a directory of your choice, and issue a single command similar to this:

```
rpm -Uhv my_dir/*.rpm
```

Where `my_dir` is a directory that you specify.

## Fresh install using the Debian package manager

On a Debian, Ubuntu, or Linux MINT computer, the order that you install the core package depends on whether you are performing a fresh installation or upgrading an existing installation. Any Centrify packages other than the core packages can be listed after the core bundle in any order.

For example, to perform a fresh installation of the core DirectControl package, you would enter commands similar to the following:

```
dpkg -i ./centrifydc-openssl-5.4.0-platform-arch.deb ./centrifydc-openldap-5.4.0-platform-arch.deb ./centrifydc-curl-5.4.0-platform-arch.deb ./centrifydc-5.4.0-platform-arch.deb
```

## Upgrading packages using the Debian package manager

If you are upgrading an existing installation, the order of the core packages is different than that in a fresh installation. Centrify packages other than the core packages can be listed after the core bundle in any order.

For example, if you were updating all of the Centrify agents, you would enter commands similar to the following, noting that the packages in **bold** are the core agent packages, and must be entered in the order below:

```
dpkg -i --force-confnew --force-confmiss --ignore-  
depends=centrifydc-nis --ignore-depends=centrifydc-  
ldapproxy --ignore-depends=centrifyda./centrifydc-  
5.4.0-platform-arch.deb ./centrifydc-openssl-5.4.0-  
platform-arch.deb ./centrifydc-openldap-5.4.0-  
platform-arch.deb ./centrifydc-curl-5.4.0-platform-  
arch.deb ./centrifydc-ldapproxy-5.4.0-platform-  
arch.deb ./centrifydc-nis-5.4.0-platform-arch.deb ./  
centrifyda-3.4.0-platform-arch.deb
```

**Note** If you do not have `centrifydc-nis`, `centrify-ldapproxy`, or `centrifyda` installed, the `--ignore-depends` command for those packages is not necessary.

The platform and architecture you specify on the file name in the command line should identify the specific operating system you are using, for example `centrifydc-5.4.0-deb7-i386.deb`. After the package manager updates the packages installed, you can optionally restart Centrify processes or reboot the computer.

You can verify the Centrify packages that were upgraded using the following command:

```
dpkg -s CentrifyDC-*
```

## Using a native package manager on UNIX computers

When you upgrade using the Centrify `install.sh` shell script, the script manages all dependencies and compatibility issues for you. If you want to upgrade Centrify software packages using the native package manager, you should first determine whether there are any compatibility issues or dependencies between the packages you have installed. You can then upgrade packages individually or simultaneously. For details about specific version compatibility requirements and upgrade scenarios, see [“Compatibility for additional packages” on page 33](#).

After you have determined whether you have any version dependencies, you can use the native package manager to upgrade all packages simultaneously. You can also use the native package manager to remove old packages individually or remove all packages simultaneously.

## Upgrading packages individually on a UNIX computer

With the exception of Solaris computers, you do not need to stop any running Centrify process to perform an upgrade on UNIX machines. On Solaris computers, you should stop all Centrify processes before upgrading. You should note that while rebooting the computer or restarting agent services after an upgrade is not required for Centrify processes in most cases, you may need to reboot the computer or restart any processes that rely on PAM or NSS modules after you complete the upgrade to ensure that the upgraded binaries and libraries are being run. Rebooting the computer after upgrade is recommended as a best practice.

To upgrade Centrify software using the native package manager, follow these basic steps:

- Stop all Centrify processes running on Solaris computers.

For example:

```
/usr/share/centrifydc/bin/centrifydc stop  
/etc/init.d/centrify-sshd stop  
/etc/init.d/adsagent stop
```

- Upgrade the core agent packages using the native package manager. The four core packages must be upgraded together.
- Upgrade other Centrify packages using the native package manager.
- Restart Centrify processes or reboot the computer.

Depending on the order in which you are upgrading individual packages, you might see warnings from the package manager about file dependencies. If you see that a dependency is generated because of a package you have yet to upgrade, it is safe to ignore the warning.

The next sections illustrate the commands to use on different platforms. The actual file name that you specify on the command line—including a specific build number, platform, and architecture—will identify the specific operating system you are updating, for example `centrifydc-5.4.0-sol8-sparc-local.tgz` or `centrifydc-5.4.0-aix53-ppc-bff.gz`.

## Performing upgrades on UNIX computers

The process for simultaneous upgrades on UNIX computers is similar to that for Linux computers. However, the native package managers on different platforms vary in their ability to perform simultaneous upgrades.

### Solaris computers

On Solaris computers, it is necessary to spool all packages that are to be installed simultaneously. The package manager can then take the spooled packages and install them all at once using one command. Before upgrading on Solaris computers, however, you should stop all Centrify processes that are running.

**Note** On Solaris 10 computers that use Solaris zones, you should upgrade the core agent packages as a separate step. You can then upgrade other Centrify packages using a simultaneous upgrade.

### To perform upgrades on Solaris computers

- 1 Stop existing Centrify processes.

For example, if you are upgrading the core agent, Centrify-enabled OpenSSH, and Centrify NIS packages, you would enter commands similar to the following:

```
/usr/share/centrifydc/bin/centrifydc stop
/etc/init.d/centrify-sshd stop

/etc/init.d/adnisd stop (on Solaris 9)

svcadm disable centrifydc_server (on Solaris 10 or later)
```

- 2 Create a new admin file.

If you are upgrading an existing installation, make a copy of the system default admin file (`/var/sadm/install/admin/default`)

and modify it to ignore dependencies. In the examples below, this file is called `my_admin`. It should look like this:

```
mail=  
instance=overwrite  
partial=nocheck  
runlevel=nocheck  
idepend=nocheck  
rdepend=quit  
space=quit  
setuid=nocheck  
conflict=nocheck  
action=nocheck  
basedir=default
```

If you are performing a fresh installation, you can use the original system admin file and keep the default settings.

- 3 Unzip and extract each package into a temporary directory, for example, `my_tmp_dir`.

To unzip and extract the agent core packages, you would enter commands similar to the following:

```
gunzip centrifydc-5.4.0-platform-arch-local.tgz  
tar xvf centrifydc-5.4.0-platform-arch-local.tar
```

```
gunzip centrifydc-openssl-5.4.0-platform-arch-  
local.tgz  
tar xvf centrifydc-openssl-5.4.0-platform-arch-  
local.tar
```

```
gunzip centrifydc-openldap-5.4.0-platform-arch-  
local.tgz  
tar xvf centrifydc-openldap-5.4.0-platform-arch-  
local.tar
```

```
gunzip centrifydc-curl-5.4.0-platform-arch-local.tgz  
tar xvf centrifydc-curl-5.4.0-platform-arch-local.tar
```

- 4 Spool the packages.

Spool the packages to a specified directory, for example, `my_spool_dir`.

To spool the core packages, you would run commands similar to the following:

```
pkgadd -s /my_spool_dir -d /my_tmp_dir/CentrifyDC
CentrifyDC
pkgadd -s /my_spool_dir -d /my_tmp_dir/CentrifyDC-
openssl CentrifyDC-openssl
pkgadd -s /my_spool_dir -d /my_tmp_dir/CentrifyDC-
openldap CentrifyDC-openldap
pkgadd -s /my_spool_dir -d /my_tmp_dir/CentrifyDC-
curl CentrifyDC-curl
```

## 5 Upgrade the packages.

To upgrade the core packages, you would enter commands similar to the following:

```
/usr/sbin/pkgadd -a my_admin -n -d /my_spool_dir
CentrifyDC-openssl
/usr/sbin/pkgadd -a my_admin -n -d /my_spool_dir
CentrifyDC-openldap CentrifyDC-curl
/usr/sbin/pkgadd -a my_admin -n -d /my_spool_dir
CentrifyDC
```

## 6 Restart Centrify processes after the upgrade is complete.

## 7 Verify the upgrade.

To verify that the upgrade was successful, run the following command:

```
/usr/bin/pkginfo | grep -i centrify
```

## HP-UX computers

On HP-UX computers, it is necessary to spool all packages that are to be installed. The package manager can then take the spooled packages and install them all at once using one command.

### To perform upgrades on HP-UX computers

#### 1 Copy and unzip all depot.gz packages into a temporary directory, for example, `my_dir`.

To unzip and extract the agent core packages, enter commands similar to the following:

```
gunzip centrifydc-5.4.0-platform-arch.depot.gz
gunzip centrifydc-openssl-5.4.0-platform-
arch.depot.gz
```

```
gunzip centrifysc-openldap-5.4.0-platform-arch.depot.gz  
gunzip centrifysc-curl-5.4.0-platform-arch.depot.gz
```

## 2 Spool each package.

On HP-UX computers, you can use the default spool directory, but you must create a working directory, for example `my_dir`.

To spool the agent core packages to `my_dir`, enter commands similar to the following:

```
swcopy -s /full_path/my_dir/centrifysc-openssl-  
5.4.0-platform-arch.depot Centrifysc-openssl  
swcopy -s /full_path/my_dir/centrifysc-openldap-  
5.4.0-platform-arch.depot Centrifysc-openldap  
swcopy -s /full_path/my_dir/centrifysc-curl-5.4.0-  
platform-arch.depot Centrifysc-curl  
swcopy -s /full_path/my_dir/centrifysc-5.4.0-  
platform-arch.depot Centrifysc
```

## 3 Upgrade the packages.

Use a single command to upgrade all packages. For example, to update the core agent packages, enter a command similar to the following:

```
swinstall -s Centrifysc-openssl Centrifysc-openldap  
Centrifysc-curl Centrifysc
```

## 4 Verify the upgrade.

Verify that the upgrade was successful by running the following commands:

```
swlist | grep -i centrifysc  
swverify Centrifysc
```

## AIX computers

On AIX computers, it is necessary to unzip all packages that are to be installed. The package manager can then take the unzipped packages and install them all at once, using one command.

### To perform upgrades on AIX computers

#### 1 Copy and Unzip the packages to a directory, for example, `my_dir`.

If you are upgrading the core agent packages, you would run commands similar to the following:

```
gunzip centrifydc-5.4.0-platform-arch-bff.gz
gunzip centrifydc-openssl-5.4.0-platform-arch-bff.gz
gunzip centrifydc-openldap-5.4.0-platform-arch-bff.gz
gunzip centrifydc-curl-5.4.0-platform-arch-bff.gz
```

## 2 Upgrade the packages.

You can now upgrade the packages using commands similar to the following:

```
inutoc .
installp -aY -d my_dir all
```

# Upgrading managed Mac OS X computers

In most cases, you can update agents on Mac OS X computers by simply installing the new agent either directly or remotely on top of an existing agent. As a best practice, you should perform in-place upgrades using a local Mac administrative (`admin`) account or any other user account that has local administrative rights and reboot the computer after completing the upgrade. In most cases, you should not perform the upgrade while you are logged on as an Active Directory user in a currently active session.

In rare cases, you might be advised to run `adflush` to clear the Active Directory cache before performing an in-place upgrade. For example, if you are updating agents from version 4.x, or earlier, to 5.1.x, run `adflush` first to ensure a smooth upgrade. It is highly unusual for an upgrade to require you to leave and rejoin a managed Mac computer to the domain.



# Compatibility for additional packages

In general, Centrify software packages are not version-dependent on each other. However, there are compatibility limitations in some situations. This chapter describes specific compatibility requirements for packages that are not part of the core agent packages or have been added to or removed from the core agent packages. If you are only upgrading the core agent packages and have no other packages installed, you can skip this chapter.

## Should you be concerned about compatibility?

Compatibility issues are managed automatically when you use the `install.sh` shell script to upgrade packages. If you plan to update packages using a native package manager, however, you should be aware of potential compatibility issues and be able to manually manage dependencies between packages. Depending on the version of Centrify software you currently have installed, the version you are upgrading to, and which packages you have installed, you might have many or no compatibility concerns. The first step is to identify which software packages and versions you have deployed.

The core agent package for access control and privilege management for versions before version 5.4.0 is `CentrifyDC`. For all releases after and including 5.4.0, the core agent package is split into four distinct packages:

```
CentrifyDC
CentrifyDC-openssl
CentrifyDC-openldap
CentrifyDC-curl
```

The core agent package for auditing is `CentrifyDA`. Other packages you might have installed include:

```
CentrifyDC-nis
CentrifyDC-krb5
CentrifyDC-ldapproxy
CentrifyDC-openssh
```

```
CentrifyDC-web  
CentrifyDC-apache  
CentrifyDC-adbindproxy
```

## Removing the CentrifyDC-samba package

If you are upgrading the core agent package for access control and privilege management and have Centrify Samba installed, you should remove the Centrify Samba (`CentrifyDC-samba`) package, install open-source Samba, and install the Centrify adbindproxy package (`CentrifyDC-adbindproxy`). See the *Samba Integration Guide* for details about that procedure.

**Note** If you are upgrading the core agent package to 5.4.0 or above, you must also upgrade `CentrifyDC-adbindproxy` to 5.4.0 or above. However, after you have upgraded the `adbindproxy` package to 5.4.0, you may not have to continue to match the version number of the core agent package for future releases.

## Compatibility for CentrifyDC-nis package

If you are upgrading the core agent packages and have the `CentrifyDC-nis` package installed, you should also upgrade the `CentrifyDC-nis` package. The `CentrifyDC-nis` package must have the same major version number as the core agent packages. The version number for the `CentrifyDC-nis` package should never be higher than the version number of the core agent packages.

Note that on some platforms, the `adnisd` package might prevent the `yppbind` service from starting properly because of the order in which services are started. For example, if `yppbind` is configured to start before the `adnisd` service, the bind will fail. This issue does not occur if you are installing new packages. However, to prevent unintended changes to the existing startup sequence during an upgrade, upgrading the `adnisd` package will not modify your existing startup configuration. You can manually correct the startup sequence after an upgrade by manually running the `chkconfig` script. For example, run the following command after the `adnisd` upgrade:

```
chkconfig adnisd on
```

## Compatibility for CentrifyDC-krb5 package

The Centrify Kerberos client tools are no longer packaged with the Centrify Server Suite agent or available from the Centrify Download Center. The client tools were formerly provided as a separate software package or as part of the core agent package to support Kerberos-based authentication on older operating systems. The package is no longer relevant on currently-supported operating systems.

## Compatibility for CentrifyDC-ldaproxy package

If you are upgrading the core agent packages and have the CentrifyDC-ldaproxy package installed, you should also upgrade the CentrifyDC-ldaproxy package. The CentrifyDC-ldaproxy package must have the same major version number as the core agent package. The version number for the CentrifyDC-ldaproxy package should never be higher than the version number of the core agent package. If you upgrade the core agent packages to a version number that is higher than the CentrifyDC-ldaproxy package version, the installation script removes the CentrifyDC-ldaproxy package. To retain the CentrifyDC-ldaproxy package when you upgrade the core agent packages, you must make sure that both packages are upgraded to the same version number.

## Compatibility for CentrifyDC-openssh package

In most cases, the core agent packages and the CentrifyDC-openssh packages are installed and upgraded together. Therefore, in most cases, they will have the same major version number. If you have the CentrifyDC-openssh package installed and are upgrading the core agent to version 5.1.2 or later, you must also upgrade the CentrifyDC-openssh package. If you use the installation script to upgrade, it enforces this compatibility requirement.

## Compatibility for CentrifDC-apache and CentrifDC-web packages

If you are upgrading the core agent packages to 5.x and have Centrif for Apache or Java applications installed, the `CentrifDC-apache` or `CentrifDC-web` package should be version 4.x or later. For example, `CentrifDC_apache-4.2.0-nnn` is compatible with CentrifDC version 5.x.

## Upgrading version-dependent packages

If you are upgrading a computer that has one or more Centrif software packages that are version-dependent on one another, you should either:

- Remove the Centrif packages that are version-dependent before upgrading the core agent packages, upgrade the core agent packages, then re-install the new versions of the version-dependent packages.
- Simultaneously upgrade the core agent packages and all of the additional packages that are version-dependent.

If you are upgrading a computer where there are no version dependencies, Centrif recommends you upgrade all packages simultaneously, if possible.

## Working with classic zones after an upgrade

Centrif Server Suite supports both classic and hierarchical zones. After you upgrade the agents, you can choose to either migrate your classic zones into a hierarchical zone structure or maintain them as classic zones. If you want to convert your classic zones into hierarchical zones, you can use the `admigrate` program. For details about using the `admigrate` program to migrate a classic zone to a new parent or child hierarchical zone, see the `man` page for `admigrate`.

Note that you can only migrate classic zones to hierarchical zones if you have upgraded the Centrif agent to version 5.x or later.

You are not required to migrate any existing classic zones. If you choose to maintain your existing zones as classic zones, however, you should be aware that the authorization model in classic zones differs from the authorization model used in hierarchical zones. For example:

- In classic zones, any user with a profile in a zone is automatically granted login access to all computers joined to the zone.
- In hierarchical zones, a user with a profile in a zone must be assigned to a role with login rights and PAM access rights before being able to login to a computer joined to a zone.

In addition, there are configuration parameters, commands, APIs, and features that are only applicable in classic zones and other parameters, commands, APIs, and features that are only applicable in hierarchical zones. For example, authorization is an optional feature that can be enabled or disabled in classic zones, so there is a configuration parameter and a zone property option to support the feature in classic zones. For hierarchical zones, authorization is required for access to any managed computer, so the configuration parameter and zone property option are not visible in hierarchical zones.

# What to do if there are problems during an upgrade

In most cases, upgrading Centrify software is a seamless process that does not interrupt services. If you are not able to complete an upgrade successfully, however, there are a few steps you can take to restore your working environment. This chapter covers the steps to take if you have problems during the upgrade process.

## Remove and re-install DirectManage Access

If you have problems upgrading any DirectManage Access components, such as DirectManage Access Manager or DirectManage Deployment Manager, you should use the Control Panel application to uninstall the software, then rerun the setup program to install the components cleanly.

If you want to restore an older version of the software—rather than attempt a fresh installation of the latest version—run the setup program for that version of the software.

## Remove and re-install DirectManage Audit

If you have problems upgrading any DirectManage Audit components, such as DirectManage Audit Manager or Centrify Audit Analyzer, you should do the following:

- Use the Control Panel application to remove the auditing infrastructure components from the local computer.
- Use ADSI Edit to remove the service connection point for the installation. If you publish this information in more than one location, remove all of the service connection points from the forest.
- Rerun the setup program to install the components cleanly.

If you want to restore an older version of the software—rather than attempt a fresh installation of the latest version—run the setup program for that version of the software.

## Remove and re-install agent features

If you have problems upgrading any agent features, such as access control and privilege management or auditing services, you should do the following:

- Log on as `root` and disable auditing on UNIX computers where auditing is enabled:  

```
dacontrol -d
```
- Use the `adleave` command to remove the UNIX computer from its current zone and Active Directory domain.
- Use the DirectAuthorize Agent Control Panel to remove the local Windows computer from its current zone, then use the Windows Control Panel application to remove the agent services from the local computer.
- Rerun the `install.sh` script or the agent setup program to install the agent cleanly.

You can join the domain from the installation script on UNIX computers or join a zone from the agent configuration wizard on Windows computers.

- Log on as `root` and enable auditing on UNIX computers where you want auditing enabled

```
dacontrol -e
```

# Index

## A

- administrative tools
  - scheduled upgrades 9
- agents
  - audit installation 17
  - backward-compatible 9
  - core and add-on packages 33
  - default packages and options 20
  - forward-compatible 9
  - group policy enforcement 10
  - install.sh 21
  - restarting 19, 25
  - updating before other components 18
  - version compatibility 13

## AIX

- simultaneous upgrades 31

audit collectors 17

audit installation

- continued communication 17
- upgrade order 16

audit store databases 17

auditing consoles 17

auditing infrastructure

- unique requirements 16
- upgrade order 16

## B

backward-compatibility 9

## C

Centrify software

- additional packages 33
- Apache support 36
- components from different versions 9
- feature sets 21
- install.sh 21
- interactive upgrades 14
- Java support 36
- native package managers 23
- removing version-dependent packages 36

- restarting after upgrade 25
- unattended upgrades 14
- upgrade order 12

Centrify website 7

conventions, documentation 6

## D

database maintenance wizard 17

Debian package manager 25

Deployment Manager 20

documentation

- additional 6
- audience 5
- conventions 6
- summary of contents 5

## G

group policies 10

## H

HP-UX

- simultaneous upgrades 30

## I

idmapper 34

installation script (install.sh)

- ADCheck diagnostic tool 21
- alternatives 11
- compatibility 33
- configuration files 22
- interactive update 21
- silent installs 22
- use of 10

interactive upgrades 14





## K

Kerberos tools 35

## L

Linux

- upgrading Centrify on 23
- using rpm 24, 25

## M

Mac OS X

- local administrator account 32

managed computers

- agent upgrades 9
- Mac OS X 32
- operating system updates 8
- verifying operations 8

management databases 17

## N

NIS package 34, 35

## O

operating systems

- native package managers 11
- platform-specific agents 10
- updates 8

## R

Red Hat Package Manager (rpm) 24, 25

## S

Samba package 34

silent installation 14

simultaneous upgrades

- AIX 31
- HP-UX 31
- Solaris 28

Solaris

- simultaneous upgrades 28
- stopping Centrify services 27
- upgrade steps 27

## U

unattended installation 14

UNIX

- dependency warnings 27
- upgrading individual packages 26

## V

versions

- effect on upgrade steps 36
- identifying dependencies 33
- mixing and matching 9

## W

Windows

- deploying from a central location 20
- interactive upgrades 14
- knowledge of 5
- unattended upgrades 14

## Z

zones

- agent compatibility 13
- authorization models 37
- hierarchical 13
- migrating 36